FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

6D Series Tractors iT4 (6105D, 6115D, 6130D, 6140D)



CAB



FRESH AIR FILTER – RE198488

RECIRCULATION FILTER – RE195491

Inspect and clean every 250 hours.
Replace every 500 hours or annually.

ENGINE



DIESEL PARTICULATE FILTER (DPF)
(6105D, 6115D) – RE568454
(6130D, 6140D) – RE551147

Service every 1500 hours.

ENGINE

SECONDARY AIR FILTER – RE253519

Replace annually. Clean as required.

ENGINE

PRIMARY AIR FILTER – SU20768

Replace annually. Clean as required.

HYDRAULICS

FILTER ELEMENT – SJ11792

Replace after 100 and then every 500 hours.

(Click here for **capacity**)



ENGINE

PRIMARY FUEL FILTER – RE541922

Replace every 500 hours.



ENGINE

OIL FILTER – RE504836

Replace after 100 and 500 hours and then every 500 hours.

If neither John Deere PLUS-50 nor an oil meeting ACEA E5 or E4 is used, carry out this service on tractors with engine serial number from 800000 every 250 hours. Engine oil must be changed at least once a year.

(Click here for **capacity**)



ENGINE

OPEN CRANKCASE VENTILATION (OCV) FILTER – DZ105796

Replace every 1500 hours.



ENGINE

FINAL FUEL FILTER – RE544394

Replace every 500 hours.

JOHN DEERE
Genuine Parts and Service

CAPACITIES
6D Series Tractors iT4 (6105D, 6115D, 6130D, 6140D)

CAPACITIES (Approximate):

Fuel Tank:

..... 158 L (41.7 gal)

Cooling System:
Cool-Gard™II Premix

6105D, 6115D..... 17.7 L (4.7 gal)
6130D, 6140D ..... 18.7 L (4.9 gal)

Crankcase with Filter:
Plus-50™II

..... 15 L (4 gal)

Transmission Case:
Hy-Gard™II

..... 58 L (15.3 gal)

MFWD Axle Housing:
GL-5

..... 5 L (1.32 gal)

MFWD Wheel Hub (Each Side):
GL-5

..... 0.8 L (0.21 gal)

Return to Filter Overview

JOHN DEERE
Genuine Parts and Service